

## Long-Reach Chain Saws



43178

- Cuts hard-to-reach branches from aerial basket or from the ground.
- Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems.
- Available in three lengths.
- Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269.
- Safety features include: two-step trigger, trigger guard, and fully covered sprocket guard.
- Anti-kickback chain and automatic chain oiler.
- Rugged high torque gear motor.

CAT. NO.	UPC NO.	DESCRIPTION
€ 43178	43178	Long Reach Chain Saw – 62.5"
38568	38568	Long Reach Chain Saw – 75"
€ 43177	43177	Long Reach Chain Saw – 88.5"
54923	54923	HTMA Male Coupler
54924	54924	HTMA Female Coupler
48337	48337	Bar Tip Guard

CAT. NO.	WEIGHT	OVERALL LENGTH
43178	8.25 lb. (3.7 kg)	62.5" (1,588 mm)
38568	8.75 lb. (4.0 kg)	75" (1,905 mm)
43177	9 lb. (4.1 kg)	88.5" (2,248 mm)

### SPECIFICATIONS

<b>Cutting Capacity</b>	13" (330 mm)
<b>System</b>	Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems
<b>Extension Type</b>	Fiberglass – tested to 100 KvA for 5 minutes
<b>Weight</b>	(see chart)
<b>Overall Length</b>	(see chart)
<b>Width</b>	4" (102 mm)
<b>Flow Range</b>	5 - 8 gpm (19 - 30 lpm)
<b>Operating Pressure</b>	1,000 - 2,000 psi (69 - 140 bar)
<b>Pressure Port Thread</b>	9/16 - 18 SAE O-Ring
<b>Return Port Thread</b>	3/4 - 16 SAE O-Ring
<b>Chain Size</b>	.325" (8.3 mm) pitch
<b>Bar Gauge</b>	.058" (1.47 mm)

## Overhead Circular Saw



\*



Not to be used for ground level operation.

- Use for high production utility line clearing and general tree clearing applications\*.
- Super Spool™ selector control for Open- and Closed-Center hydraulic systems.
- Safety features include: hand stop collar, trigger guard, two-step trigger and branch stop.
- Insulated fiberglass extension tube, tested to meet OSHA regulation 1910.269.
- Rugged gear motor.
- Angular head design makes flush cuts easier and directs chips away from the operator.
- 9" (229 mm) diameter blade standard.

CAT. NO.	UPC NO.	DESCRIPTION
43180	43180	Overhead Circular Saw*
54923	54923	HTMA Male Coupler
54924	54924	HTMA Female Coupler

### SPECIFICATIONS

<b>Cutting Capacity</b>	3.5" (89 mm)
<b>System</b>	Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems
<b>Blade Diameter</b>	9" (229 mm)
<b>Extension Type</b>	Fiberglass – tested to 100 KvA for 5 minutes
<b>Weight</b>	9 lb. (4.1 kg)
<b>Overall Length</b>	82" (2,083 mm)
<b>Flow Range</b>	4 - 6 gpm (15 - 23 lpm)
<b>Operating Pressure</b>	1,000 - 2,000 psi (69 - 140 bar)
<b>Pressure Port Thread</b>	9/16 - 18 SAE O-Ring
<b>Return Port Thread</b>	3/4 - 16 SAE O-Ring
<b>RPM</b>	5,250 rpm at 6 gpm (23 lpm)